KENTUCKY MONITORING WELL RECORD Please read all instructions prior to completing this form. Do not write in shaded area. The original copy of this form must be submitted within 30 days of well completion to the Kentucky Natural Resources and Environmental Protection Cabinet, Division of Water 8000-000 Groundwater Branch, 14 Reilly Road, Frankfort, KY 40601. Telephone (502) 564-3410. (TYPE OR PRINT CLEARLY) (2) GENERAL INFORMATION: Facility Name AAA WASTE DISPOSAL Facility Address SAME Mailing Address 14 REILLY RD (3) IDENTIFICATION NUMBER: FRANKFORT State_ 8000-0000 Zip 40601 Owner's Phone (502) 564 - 3410 USGS Quadrangle Name County Latitude Longtitude (4) WELL FRANKLIN LOCATION: FRANKFORT EAST W (5) GENERAL WELL CONSTRUCTION: (6) FACILITY TYPE: (8) PHYSIOGRAPHIC REGION: Start Date: JULY 1, 1998 Finish Date: JULY 3, 1998) RCRA () Surface Mining) CERCLA () Site Assessment) RCRA (X) Blue Grass () Ohio River Alluvium) W. Coal Field) E. Coal Field (X) Solid Waste Landfill) TSCA () Jackson Purchase Drilling Method:) Miss. Plateau () UST () Landfarm () Push/probe (X) Auger HS) Reverse Rotary (9) ATTACHMENTS: () Auger SS (X) Air Rotary) Cable Tool) Excavation () Other:) Hand Auger) Sonic Required () Mud Rotary () Other: (7) WELL USE: (check all that apply) 1. Site plan or sketch map 88 2. Well construction diagram () Dry Hole Water Quality 3. Well location) Ambient Monitoring Water Level Monitoring) Not Used On topographic map, or) Abandoned Obtained by GPS unit Depth to Bedrock: // Static Water Level: 37) Remediation) Destroyed Wellhead: () Other: 4. Laboratory analysis report () Flush Mount (X) Locking Cap () No Cap X) Stickup; inches above surface: 30 (10) WELL COMPLETION INFORMATION? (11) LITHOLOGIC LOG! Feet Below Surface Borehole Casing Feet Below Surface Diameter Diameter Casing Type From To Description 0 13 1214 4 PVC O 11 SILTY CLAY TRACE SAND 13 35 8 4 PVC 11 13 SHALE LIGHT GRAY 4 PVC SCREEN WEATHERED 13 22 LIMESTONE LIGHT GRAY DOLOMITIC 22 25 SHALE SOFT LIGHT GRAY CALCEROUS -5 45 LIMESTONE MEDIUM GRAY I.D (in.) 4 From 35 To 45 Type PVC Slot Size . 01 INTERBEDDED WITH LIGHT I.D (in.) From To Type Slot Size GRAY SHALE Annulus Fill and Seal: Feet Below Surface From 31 GROUT, CEMENT/BENTONITE BENTONITE PELLETS 33 45 SAND

(12) COMMENTS:

8 1/4 " ID HSA TO REFUSAL @ 13 FT, 8" OD ROTARY BIT 13-45 FEET,

12 FEET SAND PACK, 2 FEET BENTONITE SEAL, TREMIE GROUTED TO

SURFACE WITH CEMENT BENTONITE. 4 x 4 FT CONCRETE PAD, STEEL

PROTECTIVE CASING INSTALLED. MW-1

Drilling Company JOHN HANCOCK DRILLING	State Certification Number or Rig Operator's Number			Signature of Responsible Certified Driller		
Company Mailing Address		City	State Ky	Zip Code 40000	Date 7-6-98 Month, Day, Year	

Number of Attached Sheets 3

White Copy to Division of Water, Yellow Copy to Owner, Pink Copy to Driller's Files

DEP-8043